

[Web](#) [Images](#) [Videos](#) [Maps](#) [News](#) [Shopping](#) [Gmail](#) [more ▼](#)
[Web History](#) | [Search settings](#) | [Sign in](#)


[Advanced Search](#)

Web [Show options...](#) Results **1 - 10** of about **20,800** for **application specific grammar dom**. (0.27 seconds)

JAXB RI 1.0.4 -- Vendor Customizations

Oct 7, 2004 ... The `<xjc:dom>` customization allows you to map a certain part of the schema ... using type substitution with **application-specific** implementation classes. ... `<grammar xmlns="http://relaxng.org/ns/structure/1.0" xmlns:xjc ...`
java.sun.com/webservices/docs/1.5/.../vendorCustomizations.html - [Similar](#)

Methods and apparatus for grammar-based recognition of user ...

by A Szepesvary - 2002 - [Related articles](#)
 In step 30, the **DOM** of a **specific application** is analyzed and an **application-specific grammar** is defined. It is important to note that the defined **grammar** ...
www.freepatentsonline.com/EP1235144.html

Caching and Preparing Grammars

In order to trigger Xerces **grammar** caching, an XMLGrammarPool must be to the **grammar** pool implementation--imported grammars as well as **specific** ... How do I use this with my **application** that uses standard (SAX|DOM|JAXP) parsers? ...
xerces.apache.org/xerces2-j/faq-grammars.html - [Cached](#) - [Similar](#)

Programming Guide

In the absence of an **application-specific** panic handler, Xerces-C++ default Create a **DOM** parser XercesDOMParser parser; // Specify scanner name parser. ... Setting schema **grammar** specific features/properties will have no effect on ...
xerces.apache.org/xerces-c/program-others-3.html - [Cached](#) - [Similar](#)

[Show more results from xerces.apache.org](#)

InformIT: XML Processing with Java > Parsing XML Documents with ...

Hiding vendor-specific details with the Java API for XML Processing (JAXP) ... In addition, you can define a **grammar** through a Document Type Definition (DTD) to enforce **application-specific** syntax. ... With **DOM** processing, there are two high-level tasks: turning an XML document into a **DOM** data structure and ...
www.informit.com > [Articles](#) > [Programming](#) > [Java](#) - [Cached](#) - [Similar](#)

'Jira' Created: (XERCE-1527) Problem (bug?) with the DOMBuilder ...

with the DOMBuilder and **grammar** loading/reusing From: "Dejan Mijlkovic (JIRA)" ... Type: Bug Components: **DOM** Versions: 2.6.0 Environment: Linux knoppix Reporter: Dejan ... Since **application** that I am developing need to process many XML See the License for the **specific** language governing permissions and ...
marc.info/?i=xerces-c-dev&m=113279756322154&w=2

Modality Component to Host Environment DOM Requirements and ...

In general, these interfaces will be modality-**specific**, and defined for each component ... and updating an inline **grammar** before beginning recognition. ... The examples below possible **application-layer** constructs built upon **DOM** ...
www.w3.org/TR/modality-interface/ - [Cached](#) - [Similar](#)

Grammatical inference algorithms for the generation of visual ...

by C Crimi - 1990 - [Cited by 5](#) - [Related articles](#)